

# Ready 2Fuel

Gasoline premixed with two cycle oil

## PRODUCT DESCRIPTION

Ready 2Fuel is a mixture of premium unleaded gasoline with a high performance two cycle lubricating oil. Ready 2Fuel is designed specifically for small air-cooled two cycle gasoline engines demanding high power output. Formulated with the premium gasoline, Ready 2Fuel provides for maximum torque and minimal smoke. The unique fuel stabilizer package prevents stale gasoline formation and provides detergency. When convenient quality fuel, cleanliness and performance are your priorities Ready 2Fuel is the product of choice.

## FEATURED BENEFITS

- **Convenient sized cans match your tool's tank size - reducing waste and eliminating the need for different gasoline cans.**
- **The fuel stabilizer keeps the gasoline fresh even for extended storage.**
- **Incorporates a low smoke two cycle oil for better operation and a cleaner environment.**
- **Increased power: high octane fuel boosts torque.**
- **Accurate oil to gasoline ratios eliminate the need to guess how much oil to use. No need for 1/2 full gasoline tanks, mixing vessels, or costly and hazardous blending mistakes.**
- **Ready to go; just add to your tank.**

## TYPICAL PRODUCT SPECIFICATIONS

Gasoline Type .....	Premium Grade
Appearance/Odor .....	Green Liquid/Mild Fuel Odor
Specific Gravity, 60°F (15.6°C) .....	0.745 (typical)
Weight, lb/gal., 60°F (15.6°C).....	6.20
(Product separates upon prolonged storage and mix thoroughly prior to use.)	
Oil Ratio.....	50:1

## PERFORMANCE AND EMISSIONS

Ready 2Fuel conforms to all major 2-cycle specifications including Jasco FC and ISO EGC/EGD low smoke requirements. The Suzuki Visible Smoke Generator Test gives a very good long 85 minute SIX ratio. The ISO smoke index ratio (SIX) is defined as Index = (Candidate/Jatre 1 Reference) X 100. Similarly the lubricity (LIX) is 95 minutes while the Torque (TIX) is 98 minutes. In cleanliness tests the detergency (DIX) gives 98 minutes and the exhaust port blocking (BIX) is 90 minutes. As contrasted with Ready 2Fuel, older 2 cycle additive packages that conform to Jasco FB and ISO EGB, only produce a low (SIX) of 45 minutes and a low (BIX) of 45 minutes.

**PACKAGING**

Ready 2Fuel is available in 1 pint cans, or 1 quart cans.

**SAFETY**

Emergency and First Aid Procedures

Extremely flammable liquid; vapor may cause flash fire or explosion. Use only as a 2 cycle motor fuel.

Eye Contact - ..... If splashed into the eyes, flush with clean water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

Skin Contact - In case of contact, remove any contaminated clothing and wash the skin thoroughly with mild soap and water. If irritation persists, call a physician.

Inhalation - High concentrations of vapor may displace oxygen available for breathing. Inhalation overexposure may cause irregular heart beats. Remove to fresh air. Call a physician immediately.

Ingestion - Do not siphon by mouth. Harmful or fatal if swallowed. If ingested, call a physician immediately.

Further information regarding health and safety is available upon request.

**DOT LABELING REQUIREMENTS**

<p>Hazardous Materials Description and Proper Shipping Name (49 CFR 172.101):</p> <p>Gasohol, 3, UN 1203 PG II</p>	<p>Hazardous Class (49 CFR 172.101)</p> <p>3 DOT Class Flammable liquid</p>
--------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------